Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims

in the application:

Listing of Claims:

1 (currently amended) A tree-structured document transmitting and

receiving system having a tree-structured document transmitting apparatus and a tree-structured document receiving apparatus, said tree-

structured document transmitting apparatus having:

tree-structured document storage means of storing a plurality of tree-

structured documents:

node priority presentation means of presenting a node priority which is set

with respect to each of nodes of a tree-structured document on the basis

of the importance of an information portion to be presented from the node

to a receiving-side user while satisfying two conditions: a first condition

that the node priority of the node is equal to or lower than that of a node

which is an ancestor of that node, and a second condition that if a plurality of nodes of the same priority exist, the nodes necessarily constitute one

subtree:

node stream generation means of reading out a tree-structured document

to be transmitted from the tree-structured document storage means and

generating a node stream in which at least one of nodes and/or or

Page 4 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

subtrees are arranged in a sequence on the basis of node priorities

presented by said node priority presentation means; and

transmitting means of converting said node stream into a signal based on

a predetermined network protocol and transmitting the signal, said tree-

structured document receiving apparatus having:

receiving means of restoring the node stream from the signal received by

said predetermined network protocol from said transmitting means;

extraction means of extracting at least one of the nodes or the subtrees

from the node stream restored by said receiving means according to the

sequence of arrangement in the node stream:

reconstruction means of adding at least one of the nodes or the subtrees

in the extraction order to the tree-structured document under

reconstruction: and

display means of displaying the tree-structured document in the current

reconstructed state:

wherein said tree-structured document transmitting apparatus further has:

descendant substitute display information storage means of storing

descendant substitute display information for substitute display on said

display means of said tree-structured document receiving apparatus for

descendant nodes with respect to at least one of a node or a subtree

existing as a parent of the descendant node;

Page 5 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

descendent substitute display information addition means of making the

node stream generation means generate as said node stream a stream in

which the descendant substitute display information read out from said descendant substitute display information storage means is added

immediately after at least one of the node or the subtree existing as a

parent of the descendant node;

wherein, in said tree-structured document receiving apparatus, said

extraction means extracts at least one of the nodes or the subtrees and

the descendant substitute display information from the node stream restored by said receiving means according to the sequence of

arrangement in the node stream;

said reconstruction means adds a substitute structure portion relating to

the descendant substitute display information to the tree structure under

reconstruction in place of the descendant node relating to the descendant

substitute display information when said extraction means extracts the

descendant substitute display information; and

wherein said display means displays said descendant substitute display

2. (cancelled)

information.

3. (currently amended) The tree-structured document transmitting and

receiving system according to Claim 1 2, wherein, in said tree-structured

document receiving apparatus, said reconstruction means immediately

replaces the substitute tree-structured portion relating to the descendant

substitute display information in the tree structure under reconstruction

Page 6 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

with the descendant node when said extraction means extracts the

descendant node while substitute display for the descendant node

according to the descendant substitute display information is being

performed.

4. (previously amended) The tree-structured document transmitting and

receiving system according to Claim 1, wherein said tree-structured

document transmitting apparatus further has node priority setting means of

determining the importance of an information portion to be presented from

each node to the receiving-side user on the basis of a content of the

node, an attribute of the node, a content of the document, and attribute of

the document, the tree structure, a user instruction from a transmitting-side

user, or a user instruction from the receiving-side user, and setting a node

priority on the basis of the determination, and

wherein, in said tree-structured document transmitting apparatus, said

node priority presentation means presents the node priority set by said

node priority setting means.

5. (currently amended) A tree-structured document transmitting and

receiving system having a tree-structured document transmitting

apparatus and a tree-structured document receiving apparatus, said tree-

structured document transmitting apparatus having:

tree-structured document storage means of storing a plurality of tree-

structured documents;

a plurality of documents-by-document encoding means each assigned

processing of one tree-structured document in a plurality of tree-structured

Page 7 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

documents to be transmitted, and each having node priority presentation

means and node stream generation means, said node priority presentation

means presenting a node priority which is set with respect to each of

nodes of said assigned tree-structured document on the basis of the

importance of an information portion to be presented from the node to a

receiving-side user while satisfying two conditions: a first condition that the

node priority of the node is equal to or lower than that of a node which is

an ancestor of that node, and a second condition that if a plurality of nodes of the same priority exist, the nodes necessarily constitute one subtree.

said node stream generation means reading out a tree-structured

document to be transmitted from the tree-structured document storage

means and generating a node stream in which at least one of the nodes or

the subtrees are arranged in a sequence on the basis of node priority

presented by said node priority presentation means:

inter-document priority presentation means of presenting inter-document

priorities set as transmission priorities with respect to the plurality of tree-

structured documents to be transmitted:

multiplexed stream generation means of generating one multiplexed

stream by multiplexing the node streams from said document-by-

document encoding means, sequences in which at least one of the nodes

or the subtrees of the tree-structured documents are arranged being placed in the multiplexed stream according to the inter-document priorities

presented by said inter-document priority presentation means with respect

to the tree-structured documents containing at least one of the nodes or

the subtrees: and

Page 8 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

transmitting means of transmitting said multiplexed stream by converting said multiplexed stream on the basis of a predetermined network protocol,

said tree-structured document receiving apparatus having:

receiving means of restoring the multiplexed stream from the signal

received by said predetermined network protocol from said transmitting

means:

demultiplexing means of demultiplexing the multiplexed stream into the

plurality of node streams contained in the multiplexed stream;

a plurality of document-by-document decoding means each assigned

processing of one node stream in the plurality of node streams

demultiplexed by said demultiplexing means, and each including extraction

means and reconstruction means, said extraction means extracting the

nodes or subtrees from said processing-assigned node stream according

to the sequence of arrangement in the nodes stream, said reconstruction

means adding at least one of the node or the subtree in the extraction

order to the tree-structured document under reconstruction; and

display means of displaying the tree-structured document under

reconstruction in each document-by-document decoding means, the tree structured being displayed in the current reconstructed state at a

corresponding position;

wherein, in said tree-structured document transmitting apparatus, said

document-by-document encoding means further includes:

Page 9 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

descendant substitute display information storage means of storing descendant substitute display information for substitute display on said

display means of said tree-structured document receiving apparatus for

descendant nodes with respect to at least one of a node or a subtree

existing as a parent of the descendant node;

descendant substitute display information addition means of making the

nodes stream generation means generate as said node stream a stream in

which the descendant substitute display information read out from said

descendant substitute display information storage means is added immediately after at least one of the node or a subtree existing as a parent

of the descendant node,

wherein, in each document-by-document decoding means of said tree-

structured document receiving apparatus, said extraction means extracts

the nodes or subtrees and the descendant substitute display information from the node stream restored by said receiving means according to the

sequence of arrangement in the node stream:

said reconstruction means adds a substitute structure portion relating to

the descendant substitute display information to the tree structure under reconstruction in place of the descendant node relating to the descendant

substitute display information when said extraction means extracts the

descendant substitute display information; and

wherein said display means displays said descendant substitute display

information.

6 (cancelled)

Page 10 of 41

Appl. No. 10/667,712 Amdt. Dated October 27, 2008 Reply to Notice of October 9, 2008

- 7. (currently amended) The tree-structured document transmitted and receiving system according to Claim 5 6, wherein, in each document-by-document decoding means of said tree-structured document receiving apparatus, said reconstruction means immediately replaces the substitute tree-structured portion relating to the descendant substitute display information in the tree structure under reconstruction with the descendant node when said extraction means extracts the descendant node while substitute display for the descendant node according to the descendant substitute display information is being performed.
- 8. (previously amended) The tree-structured document transmitting and receiving system according to Claim 5, where the multiplexed stream generation means of said tree-structured document transmitting apparatus further has node priority setting means of determining the importance of an information portion to be presented from each node to the receiving-side user on the basis of a content of the node, an attribute of the node, a content of the document, an attribute of the document, the tree structure, or a user instruction, and setting a node priority on the basis of the determination, and

wherein, in the multiplexed stream generation means of said treestructured document transmitting apparatus, said node priority presentation means presents the node priority set by said node priority setting means.

 (previously amended) The tree-structured document transmitting and receiving system according to Claim 5, wherein said tree-structured document transmitting apparatus further has inter-document priority setting

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

means of setting inter-document priorities on the basis of the contents of

the documents, the attributes of the documents, the degrees of relation

with a search word relating to a search request from the receiving-side

user, a user instruction from a transmitting-side user, or a user instruction

from the receiving-side user, and

wherein, in said tree-structured document transmitting apparatus, said

inter-document priority presentation means presents the inner-document

priorities set by said inter-document priority setting means.

(cancelled)

(cancelled)

12. (cancelled)

13. (currently amended) A tree-structured document receiving

apparatus which receives a signal formed by converting on the basis of the predetermined network protocol a node stream formed in such a manner

that a node priority is set with respect to each of nodes of a tree-structured

document on the basis of the importance of an information portion to be

presented from the node to a receiving-side user while satisfying two

conditions: a first condition that the node priority of the node is equal to or

lower than that of a node which is an ancestor of that node, and a second

condition that if a plurality of nodes of the same priority exist, the nodes

necessarily constitute one subtree; and nodes or subtrees are arranged in

a sequence on the basis of the node priorities, said tree-structured

document receiving apparatus having:

Page 12 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

receiving means of restoring the node stream from the signal received by

the predetermined network protocol;

extraction means of extracting at least one of the nodes or the subtrees

from the node stream restored by said receiving means according to the

sequence of arrangement in the node stream;

reconstruction means of adding at least one of the nodes or the subtree in

the extraction order to the tree-structured document under reconstruction:

and

display means of displaying the tree-structured document in the current

reconstructed state:

wherein, in the node stream restored by said receiving means, descendant

substitute display information for substitute display on said display means

for descendant nodes with respect to at least one of a node or a subtree existing as a parent of the descendant node is added immediately after at

least one of the node or the subtree existing as a parent of the descendant

node:

said extraction means extracts at least one of the nodes or the subtrees

and the descendant substitute display information from the node stream restored by said receiving means according to the sequence of

arrangement in the node stream;

said reconstruction means adds a substitute structure portion relating to

the descendant substitute display information to the tree structure under

reconstruction in place of the descendant node relating to the descendant

Page 13 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

substitute display information when said extracting means extracts the

descendant substitute display information; and

wherein said display means displays said descendant substitute display

information.

14. (cancelled)

 (currently amended) The tree-structured document receiving apparatus according to Claim 13 44, wherein said reconstruction means

immediately replaces the substitute tree-structured portion relating to the

descendant substitute display information in the tree structure under

reconstruction with the descendant node when said extraction means extracts the descendant node while substitute display for the descendant

node according to the descendant substitute display information is being

performed.

periorified.

16. (cancelled)

17. (cancelled)

18. (cancelled)

19. (cancelled)

20. (currently amended) A tree-structured document receiving apparatus which receives a signal formed by converting on the basis of the

predetermined network protocol a multiplexed stream formed in such a

manner that a node priority is set with respect to each of nodes of a treestructured document on the basis of the importance of an information

Page 14 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

portion to be presented from the node to a receiving-side user while

satisfying two conditions: a first condition that the node priority of the node is equal to or lower than that of a node which is an ancestor of that node.

and a second condition that if a plurality of nodes of the same priority exist.

the nodes necessarily constitute one subtree; node streams are formed in

each of which, with respect to one of a plurality of tree-structured

documents to be presently transmitted, at least one of nodes or subtrees

are arranged in a sequence on the basis of the node priorities related to

the tree-structured document; and the multiplexed stream if formed by

multiplexing the node streams relating to the tree-structured documents to

be presently transmitted, sequences in which at least one of the nodes or

subtrees of the tree-structured documents are arranged being placed in

the multiplexed stream according to inter-document priorities set with

respect to the tree-structured documents containing the nodes or subtrees.

said tree-structured document receiving apparatus having:

receiving means of restoring the multiplexed stream from the signal

received by the predetermined network protocol;

demultiplexing means of demultiplexing the multiplexed stream into the

plurality of node streams contained in the multiplexed stream:

a plurality of document-by-document decoding means each assigned

processing of one node stream in the plurality of node streams

demultiplexed by said demultiplexing means, and each including extraction means and reconstruction means, said extraction means extracting the at

least one of the nodes or subtrees from said processing-assigned node

stream according to the sequence of arrangement in the nodes stream.

Page 15 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

said reconstruction means adding the node or subtree in the extraction

order to the tree-structured document under reconstruction; and

display means of displaying the tree-structured document under

reconstruction in each document-by-document decoding means, the tree structured being displayed in the current reconstructed state at a

corresponding position;

wherein, in the node stream, descendant substitute display information for

substitute display on said display means for descendant nodes with respect to at least one of a node or a subtree existing as a parent of the

descendant node is added immediately after at least one of the node or

the subtree existing as a parent of the descendant node;

said extraction means in said document-by-document decoding means

extracts at least one of the nodes or the subtrees and the descendant substitute display information from the node stream according to the

sequence of arrangement in the node stream;

said reconstruction means in said document-by-document decoding

means adds a substitute structure portion relating to the descendant

substitute display information to the tree structure under reconstruction in place of the descendant node relating to the descendant substitute display

information when said extraction means extracts the descendant substitute

display information; and

wherein said display means displays said descendant substitute display

information.

Page 16 of 41

Amdt. Dated October 27, 2008 Reply to Notice of October 9, 2008

## 21. (cancelled)

22. (currently amended) The tree-structured document receiving apparatus according to Claim 20 24, wherein said reconstruction means in said document-by-document decoding mean immediately replaces the substitute tree-structured portion relating to the descendant substitute display information in the tree structure under reconstruction with the descendant code when said extraction means extracts the descendant node while substitute display for the descendant node according to the descendant substitute display information is being performed.

23. (currently amended) A tree-structured document transmitting and receiving method having a tree-structured document transmitting method and a tree-structured document receiving method, said tree-structured document transmitting method having:

a node stream generation step of generating a node stream in such a manner that a node priority is set with respect to each of nodes of a tree-structured document on the basis of the importance of an information portion to be presented from the node to a receiving-side user while satisfying two conditions: a first condition that the node priority of the node is equal to or lower than that of a node which is an ancestor of that node, and a second condition that if a plurality of nodes of the same priority exist, the nodes necessarily constitute one subtree; a tree-structured document to be transmitted is read out from tree-structured document storage means; and at least one of the nodes or the subtrees of the tree-structured document are arranged in a sequence on the basis of said node priorities; and

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

a transmitting step of converting said node stream into a signal based on a

predetermined network protocol and transmitting the signal, said tree-

structured document receiving apparatus having:

a receiving step of restoring the node stream from the signal received by

said predetermined network protocol:

an extraction step of extracting at least one of the nodes or the subtrees

from the node stream restored by said receiving means according to the

sequence of arrangement in the node stream;

a reconstruction step of adding at least one of the extracted nodes or the

subtree in the extraction order to the tree-structured document under

reconstruction; and

a display step of displaying on the display means the tree-structured

document in the current reconstructed state:

wherein said tree-structured document transmitting apparatus further has:

a descendant substitute display information addition step of generating, in

the node stream generation step, as said node stream, a node stream in

which descendant substitute display information for substitute display on

display means on the receiving side for descendant nodes with respect to

at least one of a node or a subtree existing as a parent of the descendant

 $\underline{\text{node}}$  is added immediately after at least one of the node or the subtree

existing as a parent of the descendant node,

wherein, in said tree-structured document receiving method, said

extraction step comprises extracting at least one of the nodes or the

Page 18 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

subtrees and the descendant substitute display information from the node stream restored in said receiving step according to the sequence of

arrangement in the node stream:

said reconstruction step comprises adding a substitute structure portion

relating to the descendant substitute display information to the tree

structure under reconstruction in place of the descendant node relating to the descendant substitute display information when the descendant

substitute display information is extracted in said extraction step; and

wherein said display step comprises displaying on the display means the

descendant substitute display information.

24. (cancelled)

25. (currently amended) The tree-structured document transmitting and

receiving method according to Claim 23 24, wherein, in said tree-

structured document receiving method, said reconstruction step comprises  $\label{eq:construction}$ 

immediately replacing the substitute tree-structured portion relating to the descendant substitute display information in the tree structure under

reconstruction with the descendant node when the descendant node is

extracted in said extraction step while substitute display for the

descendant node according to the descendant substitute display

information is being performed.

26. (previously amended) The tree-structured document transmitting and

receiving method according to Claim 23, wherein said tree-structured document transmitting method as a node priority setting step of setting

node priorities used in the node stream generation step, and

Page 19 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

wherein, in said node priority setting step, the importance of an information

portion to be presented from each node to the receiving-side user is determined on the basis of a content of the node, an attribute of the node.

a content of the document, an attribute of the document, the tree structure.

a user instruction from a transmitting-side user, or a user instruction from

the receiving-side user, and a node priority is set on the basis of the

the receiving-side user, and a node priority is set on the t

determination.

27. (currently amended) A tree-structured document transmitting and

receiving method having a tree-structured document transmitting method

and a tree-structured document receiving method, said tree-structured

document transmitting method having:

a plurality of document-by-document encoding steps each assigned

processing of one tree-structured document in a plurality of tree-structured

documents to be transmitted, and each including a node stream

generation substep comprising generating a node stream in such a

manner that a node priority is set with respect to teach of nodes of a tree-

structured document on the basis of the importance of an information

portion to be presented from the node to a receiving-side user while

satisfying two conditions: a first condition that the node priority of the node

is equal to or lower than that of a node which is an ancestor of the node.

and a second condition that if a plurality of nodes of the same priority exist,

the nodes necessarily constitute one subtree; one assigned tree-structured

document is read out from tree-structured document storage means; and

at least one of the nodes or the subtrees of the tree-structured document

are arranged in a sequence on the basis of said node priorities;

Page 20 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

a multiplexed stream generation step of generating one multiplexed

stream by multiplexing the node streams in said document-by-document

encoding steps, inter-document priorities being set as transmission

priorities with respect to the plurality of tree-structured documents to be

transmitted, sequences in which at least one of the nodes or the subtrees

of the tree-structured documents are arranged being placed in the

multiplexed stream according to the inter-document priorities with respect

to the tree-structured documents; and

a transmitting step of transmitting said multiplexed stream by converting

said multiplexed stream on the basis of a predetermined network protocol.

said tree-structured document receiving method having:

a receiving step of restoring the multiplexed stream from the signal

received by the predetermined network protocol:

a demultiplexing step of demultiplexing the multiplexed stream into the

plurality of node streams contained in the multiplexed stream:

a plurality of document-by-document decoding means each assigned

processing of one node stream in the plurality of node streams demultiplexed by said demultiplexing step, and each including extraction

substep and reconstruction substep, said extraction substep comprising

extracting at least one of the nodes or the subtrees from said processing-

assigned node stream according to the sequence of arrangement in the

nodes stream, said reconstruction substep comprising adding at least one

of the node or the subtree extracted in said extraction substep in the

extraction order to the tree-structured document under reconstruction; and

Page 21 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

a display step of displaying the tree-structured document under

reconstruction in each document-by-document decoding step, the tree

structured being displayed in the current reconstructed state at a

corresponding position of the display means;

wherein, in said tree-structured document transmitting method, said

document-by-document encoding step further includes:

a descendant substitute display information addition substep of

generating, in the node stream generation step, as said node stream, a

node stream in which descendant substitute display information for

substitute display on said display means on the receiving side for

descendant nodes with respect to at least one of a node or a subtree

existing as a parent of the descendant node is added immediately after at

least one of the node or the subtree existing as a parent of the descendant

node;

wherein, in said tree-structured document receiving method, said

extraction substep in each document-by-document decoding step

comprises extracting at least one of the nodes or the subtrees and the

descendant substitute display information from the node stream restored by said receiving step according to the sequence of arrangement in the

node stream:

said reconstruction substep in each document-by-document decoding step

of said tree-structured document receiving method comprises adding a

substitute structure portion relating to the descendant substitute display

information to the tree structure under reconstruction in place of the

Page 22 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

descendant node relating to the descendant substitute display information when said the descendant substitute display information is extracted in

said extraction substep; and

wherein said display step comprises displaying on the display means the

descendant substitute display information.

28. (cancelled)

29. (currently amended) The tree-structured document transmitted and

receiving method according to Claim 27 28, wherein, in each treestructured document receiving method, said reconstruction substep in

each document-by-document decoding step comprises immediately

replacing the substitute tree-structured portion relating to the descendant

substitute display information in the tree structure under reconstruction

with the descendant node when the descendant node is extracted in said

extraction substep while substitute display for the descendant node

according to the descendant substitute display information is being

performed.

30. (previously amended) The tree-structured document transmitting and

receiving method according to Claim 27, wherein the multiplexed stream

generation step of said tree-structured document transmitting method

includes a node priority setting substep of setting node priorities used in

the node stream generation substep, and

wherein, in said node priority setting substep, the importance of an

information portion to be presented from each node to the receiving-side

user is determined on the basis of a content of the node, an attribute of the

Page 23 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

node, a content of the document, and attribute of the document, the tree structure, or a user instruction, and a node priority is set on the basis of

the determination

31. (previously amended) The tree-structured document transmitting and

receiving method according to Claim 27, wherein said tree-structured

document transmitting method further has an inter-document priority setting step of setting inter-document priorities on the basis of the contents

of the documents, the attributes of the documents, the degrees of relation

with a search word relating to a search request from the receiving-side

user, a user instruction from a transmitting-side user, or a user instruction

from the receiving-side user, and

wherein, in said tree-structured document transmitting method, said

multiplexed stream generation step comprises restoring the multiplexed

stream on the basis of the inter-document priorities set in said inter-

document priority setting step.

(cancelled)

(cancelled)

34. (cancelled)

35. (currently amended) A tree-structured document receiving method

of receiving a signal formed by converting on the basis of the

predetermined network protocol a node stream formed in such a manner

that a node priority is set with respect to each of nodes of a tree-structured document on the basis of the importance of an information portion to be

Page 24 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

presented from the node to a receiving-side user while satisfying two

conditions: a first condition that the node priority of the node is equal to or

lower than that of a node which is an ancestor of that node, and a second

condition that if a plurality of nodes of the same priority exist, the nodes

necessarily constitute one subtree; and at least one of the nodes or the

subtrees are arranged in a sequence on the basis of the node priorities,

said tree-structured document receiving method apparatus having:

a receiving step of restoring the node stream from the signal received by

the predetermined network protocol;

an extraction step of extracting at least one of the nodes or the subtrees

from the node stream restored in said receiving step according to the

sequence of arrangement in the node stream;

a reconstruction step of adding at least one of the extracted nodes or the

subtree in the extraction order to the tree-structured document under

reconstruction; and

a display step of displaying the tree-structured document in the current

reconstructed state:

wherein, in the node stream restored in said receiving step, descendant

substitute display information for substitute display on said display means

for descendant nodes with respect to at least one of a node or a subtree

existing as a parent of the descendant node is added immediately after at least one of the node or the subtree existing as a parent of the descendant

node;

Page 25 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

said extraction step comprises extracting at least one of the nodes or the

subtrees and the descendant substitute display information from the node

stream restored in said receiving step according to the sequence of

arrangement in the node stream;

said reconstruction step comprises adding a substitute structure portion

relating to the descendant substitute display information to the tree structure under reconstruction in place of the descendant node relating to

the descendant substitute display information when the descendant

substitute display information is extracted in said extraction step; and

wherein said display step comprises displaying on the display means the

descendant substitute display information.

(cancelled)

37. (currently amended)The tree-structured document receiving method

according to Claim 35 36, wherein said reconstruction step comprises

immediately replacing the substitute tree-structured portion relating to the

descendant substitute display information in the tree structure under

reconstruction with the descendant node when the descendant node is

extracted in said extraction step while substitute display for the descendant node according to the descendant substitute display

information is being performed.

38. (cancelled)

39. (cancelled)

40. (cancelled)

Page 26 of 41

Appl. No. 10/667,712 Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

## 41. (cancelled)

42. (currently amended) A tree-structured document receiving method of receiving a signal formed by converting on the basis of the predetermined network protocol a multiplexed stream formed in such a manner that a node priority is set with respect to each of nodes of a treestructured document on the basis of the importance of an information portion to be presented from the node to a receiving-side user while satisfying two conditions: a first condition that the node priority of the node is equal to or lower than that of a node which is an ancestor of that node. and a second condition that if a plurality of nodes of the same priority exist, the nodes necessarily constitute one subtree; node streams are formed in each of which, with respect to one of a plurality of tree-structured documents to be presently transmitted, at least one of nodes or subtrees are arranged in a sequence on the basis of the node priorities related to the tree-structured document; and the multiplexed stream is formed by multiplexing the node streams relating to the tree-structured documents to be presently transmitted, sequences in which at least one of the nodes or the subtrees of the tree-structured documents are arranged being placed in the multiplexed stream according to inter-document priorities set with respect to the tree-structured documents containing at least one of the nodes or the subtrees, said tree-structured document receiving method apparatus having:

a receiving step of restoring the multiplexed stream from the signal received by the predetermined network protocol:

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

a demultiplexing step of demultiplexing the multiplexed stream into the

plurality of node streams contained in the multiplexed stream;

a plurality of document-by-document decoding means each assigned

processing of one node stream in the plurality of node streams

demultiplexed in said demultiplexing step, and each including an extraction

substep and a reconstruction substep, said extraction substep comprising

extracting at least one of the nodes or the subtrees from said processing-

assigned node stream according to the sequence of arrangement in the

nodes stream, said reconstruction substep comprising adding the node or

subtree extracted in said extraction substep in the extraction order to the

tree-structured document under reconstruction; and

a display step of displaying the tree-structured document under

reconstruction in each document-by-document decoding step, the tree

structured being displayed in the current reconstructed state at a

corresponding position of the display means:

wherein, in the node stream, descendant substitute display information for

substitute display on said display means for descendant nodes with

respect to at least one of a node or a subtree existing as a parent of the descendant node is added immediately after at least one of the node or

the subtree existing as a parent of the descendant node:

said extraction substep in said document-by-document decoding step

comprises extracting at least one of the nodes or the subtrees and the

descendant substitute display information from the node stream according

to the sequence of arrangement in the node stream;

Page 28 of 41

Amdt. Dated October 27, 2008

Reply to Notice of October 9, 2008

said reconstruction substep in said document-by-document decoding step comprises adding a substitute structure portion relating to the descendant substitute display information to the tree structure under reconstruction in place of the descendant node relating to the descendant substitute display

information when the descendant substitute display information is

extracted in said extraction substep; and

wherein said display step comprises displaying on the display means the descendant substitute display information.

## 43. (cancelled)

44. (currently amended) The tree-structured document receiving method according to Claim 42 43, wherein said reconstruction substep in said document-by-document decoding step comprises immediately replacing the substitute tree-structured portion relating to the descendant substitute display information in the tree structure under reconstruction with the descendant node when the descendant node is extracted in said extraction substep while substitute display for the descendant node according to the descendant substitute display information is being performed.

## 45. (new) A method comprising:

transmitting a sequence of portions of a document, said document including information defining document symbols and the location of said document symbols on a page;

Amdt. Dated October 27, 2008 Reply to Notice of October 9, 2008

receiving some of said transmitted sequence of portions of said document;

displaying said received portions of said document; and displaying substitute symbols in locations corresponding to portions of said document that have not been received.

46. (new) A method according to claim 45 wherein said displaying comprises displaying a repeated character in said locations corresponding to portions of said document that have not been received.